



Promotora Industrial de Desarrollo, S. A. de C. V. | Calle Cocoteros Lote 5 Mz. 16 | Cd. Industrial Bruno
Pagliai 91697 | Veracruz | México | T. +52-229-927-2437 | sales_dpt@camex.lat | www.pid.com.mx

FORESTRY TRAILERS GENERAL SPECIFICATIONS

	CODE*	CX2005	CX2205	CX2207	CX2209	CX2610
WEIGHT		995 lb/ 451 Kg	1185 lb/ 537 Kg	1565 lb/ 710 Kg	1645 lb/ 746 Kg	1907 lb/ 856Kg
CAPACITY (GVWR)		3T/ 6614 lb	5T/ 11 023 lb	7T/ 15 432 lb	9T/ 19 842 lb	12T/ 26 456 lb
RECOMMENDED FOR		Tractor 30 HP	Tractor 40 HP	Tractor 50 HP	Tractor 75 HP	Tractor 100 HP
OVERALL LENGTH	F	190"	190"	211"	211"	240"
OVERALL WIDTH	A	65½"	65½"	84½"	84½"	84"
HEIGHT OF POSTS	B	41"	41"	42"	42"	42"
COUPLER HEIGHT	D	12"	12"	14"	14"	15"
LOADING LENGTH	E	120"	120"	141"	141"	170"
LOADING WIDTH	C	60"	60"	73"	73"	73"
BASE WIDTH	G	30"	30"	44"	44"	44"
TRACK CENTER/CENTER	H	56½"	56½"	68½"	68½"	69"
ROAKING LENGHT	I	147½"	147½"	148"	148"	160"
GRID HEIGHT	J	43"	43"	49"	49"	49"
GROUND CLEARANCE	K	21"	21"	23"	23"	24"
OVERALL HEIGHT	L	64"	64"	71"	71"	73"
GRID WIDTH	M	57"	57"	72"	72"	72"
GRID CLEARANCE	N	70"	70"	70"	70"	70"
SUPPORT CLEARANCE	O	31"	31"	31"	31"	31"
SPINDLES		2"	2"	2"	2"	2"
HUB HOLES		6 holes	6 holes	6 holes	6 holes	8 holes
AGRICULTURAL TIRES		11L15 8 ply	11L15 8 ply	12L15 10ply	12L15 10ply	14L16 12ply
SUPPORT		ADJUSTABLE POSITION	ADJUSTABLE POSITION	ADJUSTABLE POSITION	ADJUSTABLE POSITION	ADJUSTABLE POSITION
TANDEM		3 ADJUSTABLE POSITIONS	3 ADJUSTABLE POSITIONS	3 ADJUSTABLE POSITIONS	3 ADJUSTABLE POSITIONS	3 ADJUSTABLE POSITIONS
ELECT OR HYDR.		12"	12"	12"	12"	12"
OPTIONS:						
ELECTRIC OR HYDRAULIC BRAKE						
WHEEL DEFLECTOR						

